

# IRONCORE

## STOCK LIST

DOUBLE WOUND – LAYER INSULATED – CONTINUOUSLY RATED – QUALITY CONTROLLED

### TRANSFORMER RECTIFIERS (Enclosed with Fused Secondary)

TYPE	DESCRIPTION PRIMARY- SECONDARY	RATING WATTS OR V.A.	L x W x H SIZE – mm	FINISH SEE KEY	APPROX WEIGHT kg
T6-1607	240VAC-12VDC	84WATT 7A	130x95x130	F	3.7
T6-1607	240VAC-12VDC	84 WATT 7A	205x115x160	E	5.5
T6-2103	240VAC-12VDC	120 WATT 10A	263x147x160	E	6.5
T6-2016	240VAC-24VDC	100 WATT 4.16A	140x100x140	F	4.5
T6-2016	240VAC-24VDC	100 WATT 4.16A	264x150x160	E	5.0
T9-1094	240VAC-24VDC	200 WATT 8.33A	180x100x175	F	8.5
T9-1094	240VAC-24VDC	200 WATT 8.33A	260x165x195	E	10.5

### TRANSFORMER RECTIFIERS (Non-Standard Range) DC

240VAC-12VDC	20 WATT 1.66A	F
	200 WATT 16.66A	F
	300 WATT 25.00A	F
	500 WATT 41.56A	F
	1000 WATT 83.33A	F
240VAC-24VDC	500 WATT 20.83A	F
	1000 WATT 41.66A	F

NOT EX- STOCK

### SAFETY LEAD LIGHT TRANSFORMERS

T6-78	240V-32V (2 Outlets)	120 VA	185x190x145	C	5.0
T6-801	240V-12V (2 Outlets)	120 VA	190x130x150	C	5.0

### STEP DOWN TRANSFORMERS (STEP UP Prices on Application)

T1-66	240V-6V	30 VA	133x79x95	F	1.5
T1-66	240V-6V	30 VA	80x135x95	A	1.9

T3-50	240V-12V	24 VA	75x75x100	F	1.3
T3-50	240V-12V	24 VA	75x130x80	A	1.5
T1-68	240V-12V	60 VA	65x78x110	F	2.0
T1-1414(T6-578)	240V-12V	100 VA	80x75x110	F	1.8
T1-1414(T6-578)	240V-12V	100 VA	152x95x114	A	3.2
T6-642	240V-12V	200 VA	95x120x140	F	6.0
T6-642	240V-12V	200 VA	195x125x155	E	5.0

T8-62	240V-24V	10 VA	44x76x44	F	0.5
T5-46	240V-24V	30 VA	65x80x95	F	1.0
T5-46	240V-24V	30 VA	135x100x125	E	1.0
T1-880	240V-24V	60 VA	80x75x115	F	2.0
T1-880	240V-24V	60 VA	140x79x95	A	2.0
T1-880	240V-24V	60 VA	130x100x125	E	2.3
T1-1558(T6-98)	240V-24V	100 VA	80x85x115	F	3.0
T1-1558(T6-98)	240V-24V	100 VA	152x95x114	A	3.5

#### KEY TO FINISH

A - METAL COVERS 'T' PIN OUTLET  
 B - METAL COVERS 2 PIN OUTLET  
 C - PORTABLE METAL CASE 'T' PIN OUTLET (sec.under 50v)  
 D - PORTABLE METAL CASE 2 PIN OUTLET (sec.over 50v)

E - METAL CASE CONDUIT ENTRY (enclosed)  
 F - OPEN TYPE TERMINALS  
 F/S-OPEN TYPE WITH SHIELD  
 G - PORTABLE CASE 3 PIN OUTLET  
 (Sec. over 240v)

# IRONCORE

## STOCK LIST

DOUBLE WOUND – LAYER INSULATED – CONTINUOUSLY RATED – QUALITY CONTROLLED

### STEP DOWN TRANSFORMERS

TYPE	DESCRIPTION PRIMARY- SECONDARY	RATING WATTS OR V.A.	L x W x H SIZE – mm	FINISH SEE KEY	APPROX WEIGHT kg	TRADE PRICE EX-FACTORY
T6-782	240V-24V	150 VA	95X110X135	F	4.1	
T6-72	240V-24V	200 VA	95X130X135	F	5.0	
T6-72	240V-24V	200 VA	190X125X155	E	5.2	
T9-866	240V-24V	300 VA	114X127X165	F	6.8	
T9-866	240V-24V	300 VA	260X161X195	E	7.0	
T9-270	240V-24V	500 VA	127X127X165	F	12.0	
T9-270	240V-24V	500 VA	260X161X195	E	13.8	
T10-397	240V-24V	1000 VA	203X152X178	F	15.0	
T10-397	240V-24V	1000 VA	310X172X190	E	15.5	
T3-36	240V-32V	20 VA	73X65X190	F	1.0	
T3-36	240V-32V	20 VA	73x180x80	A	1.1	
T1-62	240V-32V	40 VA	80X70X115	F	2.0	
T1-62	240V-32V	40 VA	137X79X95	A	2.0	
T1-64	240V-32V	75 VA	76X83X114	F	2.0	
T1-64	240V-32V	75 VA	146X79X95	A	2.7	
T1-1559(T6-56)	240V-32V	100 VA	80x70x110	F	2.0	
T1-1559(T6-56)	240V-32V	100 VA	152X95X114	A	3.5	
T1-1559(T6-56)	240V-32V	100 VA	185X125X155	C	4.2	
T6-42	240V-32V	150 VA	102X95X133	F	4.1	
T6-42	240V-32V	150 VA		E		
T6-42	240V-32V	150 VA	165X95X114	A	5.0	
T6-42	240V-32V	150 VA	185X125X155	C	6.4	
T6-44	240V-32V	200 VA	114X95X130	F	5.5	
T6-44	240V-32V	200 VA	184X95X114	A	5.5	
T6-44	240V-32V	200 VA	185X125X155	C	6.4	
T9-30	240V-32V	300 VA	114X127X165	F	6.8	
T9-30	240V-32V	300 VA	260X161X195	E	9.5	
T9-30	240V-32V	300 VA	245X162X205	C	9.5	
ST-2	240V-32V	500 VA	127X127X165	F	13.6	
ST-2	240V-32V	500 VA	260X161X195	E	13.6	
ST-2	240V-32V	500 VA	245X162X205	C	13.6	
ST-4	240V-32V	750VA	160X140X220	F		
ST-4	240V-32V	750 VA	310X172X190	E	14.0	
ST-4	240V-32V	750 VA	305X175X212	C	15.0	
ST-6	240V-32V	1000 VA	203X140X178	F	14.5	
ST-6	240V-32V	1000 VA	310X172X190	E	15.0	
T13-37(ST-8)	240V-32V	2000 VA	300X245X300	E	26.0	

#### KEY TO FINISH

A – METAL COVERS 'T' PIN OUTLET

B – METAL COVERS 2 PIN OUTLET

C – PORTABLE METAL CASE 'T' PIN OUTLET (sec.under 50v)

D – PORTABLE METAL CASE 2 PIN OUTLET (sec.over 50v)

E – METAL CASE CONDUIT ENTRY (enclosed)

F – OPEN TYPE TERMINALS

F/S–OPEN TYPE WITH SHIELD

G – PORTABLE CASE 3 PIN OUTLET  
(Sec. over 240v)

# IRONCORE

## STOCK LIST

DOUBLE WOUND – LAYER INSULATED – CONTINUOUSLY RATED – QUALITY CONTROLLED

### STEP DOWN TRANSFORMERS

TYPE	DESCRIPTION PRIMARY- SECONDARY	RATING WATTS OR V.A.	L x W x H SIZE – mm	FINISH SEE KEY	APPROX WEIGHT kg	TRADE PRICE EX-FACTORY
T3-14	240V-110V	20 VA	75X65X95	F		
T3-14	240V-110V	20 VA	114X73X81	B	1.2	
T1-30	240V-110V	40 VA	80X80X110	F	2.0	
T1-30	240V-110V	40 VA	80X135X95	B	2.0	
T1-60	240v- 110V	75 VA	80X75X115	F	2.0	
T1-1560(T6-6)	240V-110V	100 VA	80X75X115	F	1.9	
T1-1560(T6-6)	240V-110V	100 VA	145X95X114	B	3.6	
T1-1560(T6-6)	240V-110V	100 VA	190X125X155	D	4.0	
T6-8	240V-110V	150 VA	95X80X135	F	4.1	
T6-8	240V-110V	150 VA	159X95X114	B	5.0	
T6-8	240V-110V	150 VA	190X125X125	D	5.0	
T6-10	240V-110V	200 VA	108X95X133	F	5.5	
T6-10	240V-110V	200 VA	185X125X155	E	5.5	
T6-10	240V-110V	200 VA	184X95X114	B	6.0	
T6-10	240V-110V	200 VA	190X125X155	D	6.4	
T6-70	240V-110V	300 VA	95X130X130	F	7.0	
T6-70	240V-110V	300 VA	191X95X144	B	7.5	
T6-70	240V-110V	300 VA	225X112X159	E	8.2	
T6-70	240V-110V	300 VA	191X120X155	D	8.2	
ST-14	240V-110V	500 VA	130X150X170	F	11.0	
ST-14	240V-110V	500 VA	260X161X195	E	13.0	
ST-14	240V-110V	500 VA	245X162X205	D	13.0	
ST-16	240V-110V	750 VA	310X172X190	F	14.0	
ST-16	240V-110V	750 VA	310X172X190	E	14.5	
ST-16	240V-110V	750 VA	305X175X212	D	16.0	
ST-18(T10-18)	240V-110V	1000 VA	205x130x195	F	14.5	
ST-18(T10-18)	240V-110V	1000 VA	320X180X200	E	17.5	
ST-18(T10-18)	240V-110V	1000 VA	288x175x195	D	17.0	
ST-630(T13-31)	240V-110V	1500 VA	300X245X300	F	21.0	
ST-630(T13-31)	240V-110V	1500 VA	300X245X300	E	22.0	
St-20(T13-32)	240V-110V	2000 VA	190X135X250	F	30.0	
St-20(T13-32)	240V-110V	2000 VA	300X245X300	E	32.0	
T1-1	415V-24V	40 VA	80X70X115	F	1.8	
T1-11	415V-24V	75 VA	80X70X115	F	2.0	
T1-1573(T6-921)	415V-24V	100 VA	80x90X115	F	1.9	
T6-287	415V-24V	200 VA	95X130X135	F	6.0	
T9-427	415V-24V	300 VA	127X135X180	F		
T9-922	415V-24V	500 VA	127X150X180	F	11.0	
T10-241	415V-24V	1000 VA	203X160X180	F	14.5	

DOUBLE WOUND – LAYER INSULATED – CONTINUOUSLY RATED – QUALITY CONTROLLED

### STEP DOWN TRANSFORMERS

TYPE	DESCRIPTION PRIMARY- SECONDARY	RATING WATTS OR V.A.	L x W x H SIZE – mm	FINISH SEE KEY	APPROX WEIGHT kg	TRADE PRICE EX-FACTORY
T1-296	415V-32V	75 VA	76X79X114	F	2.2	\$105.00
T1-296	415V-32V	75 VA	135X100X125	E	3.0	\$132.00
T1-296	415V-32V	75 VA	140X79X95	A	2.5	\$132.00
T1-1567(T6-94)	415V-32V	100 VA	80X85X115	F	1.9	\$127.00
T1-1567(T6-94)	415V-32V	100 VA	146X95X115	A	3.4	\$154.00
T6-838	415V-32V	150 VA	111X95X133	F	4.1	\$138.00
T6-333	415V-32V	200 VA	121X95X133	F	6.0	\$157.00
T9-3	415V-32V	300 VA	114X127X165	F	6.8	\$205.00
T9-264	415V-32V	500 VA	130X150X175	F	12.0	\$280.00

T1-1566(T6-514)	415V-110V	100 VA	80x75X115	F	1.9	\$127.00
T6-902	415V-110V	150 VA	102X95X133	F	4.1	\$138.00
T6-1574	415V-110V	200 VA	95X120X135	F	5.5	\$157.00

T9-460	415V-110V	300 VA	110X140X160	F	6.8	\$207.00
T9-238	415V-110V	500 VA	130X140X170	F	11.4	\$308.00
T10-246	415V-110V	1000 VA	205X130X175	F	14.5	\$341.00

T1-1574(T6-626)	415V-240V	100 VA	80x75x115	F	1.9	\$126.00
T1-1574(T6-626)	415V-240V	100 VA	80X72X115	E	2.0	\$154.00
T6-402	415V-240V	200 VA	121X95X133	F	5	\$166.00
T6-402	415V-240V	200 VA		E		\$193.00
T9-284	415V-240V	500 VA	140X127X165	F	11.4	\$279.00
T10-162	415V-240V	1000 VA	203X110X178	F	14.5	\$341.00

### ISOLATION TRANSFORMERS

T9-1632	240V-240V	250 VA	130X105X175	F/S	5.0	\$212.00
T9-1633	240V-240V	500 VA	130X140X175	F/S	11.0	\$330.00
T15-8	240V-240V	1000 VA	220X160X195	F/S	18.0	\$440.00

## TRANSFORMERS

**SINGLE PHASE AND 3 PHASE DOUBLE WOUND**

**RANGE UP TO 800 KVA**

**(PRICES ON APPLICATION)**

***SUPPLIERS TO MAJOR INDUSTRY AND GOVERNMENT  
PROJECTS***

***QUALITY AND RELIABILITY ASSURED***